



AWNMAX AWNING FABRIC MAINTENANCE

Congratulations on purchasing the most popular awning vinyl on the market.

First, the reinforced scrim of AWNMAX is treated for anti-wicking, so soiling and mildew in the fabric are virtually eliminated.

Second, the hard acrylic top-coat allows for easier cleaning. The smooth surface does not provide grooves for contaminants to adhere to, and regular intervals of cleaning with mild soap and water will provide maximum performance. Cleaning should be done every 2-3 months, or as required depending on the surrounding environment.

It's also important that the awning is well ventilated to allow any moisture that may accumulate (due to weather conditions or cleaning) to dry properly.

POLYLEN cleaner is recommended for awning material that has been allowed to stain. It is available through the manufacturer of your awning.

Solvents such as alcohol, petroleum, or silicone-based products must never be used when cleaning. There is no replacement for factory applied topcoat. These chemicals destroy the top-coating, thus aging the fabric prematurely. Some cleaning companies will recommend stripping, sealing and top dressing your awning. Sealants or other top dressing should never be used as the fabric has factory applied sealant, which will be destroyed, leaving the fabric exposed to the elements and voiding the warranty.

Awnmax awnings that are well maintained have been known to last many years beyond the warranty period without showing excessive colour, loss or wear.